


DROP PACKERS

TOP LOAD CASE PACKING



DPI DROP PACKER

With Independent Case and Product Feed

DROP PACKER MODELS

| SPECIFICATIONS | DPI | DPI XL | DP 10 | DP 12 | DP 15 | DP 19 | DP 20 |
|---------------------------------|--|------------------------|-------------------------|--------------------------|-------------------------|--------------------------|-------------------------|
| Integrated Case Erector | N | N | Y | Y | Y | Y | Y |
| Bottom Case Sealing | N/A | N/A | N | N | Y | N | Y |
| Max. Speed | 25-50 CPM | 25-50 CPM | 10 CPM | 12 CPM | 15 CPM | 19 CPM | 20 - 30 CPM |
| Max. Case Range | 20" x 14" x 18" OAH | 24" x 16" x 18" OAH | 24" x 16" x 18" OAH | 20" x 13.5" x 18" OAH | 24" x 16" x 18" OAH | 16" x 10" x 18" OAH | 24" x 16" x 18" OAH |
| Min. Case Range | 8" x 6" x 5" | 8" x 6" x 5" | 13" x 7.75" x 6" | 8.5" x 4.75" x 4" | 8" x 6" x 5" | 8" x 6" x 5" | 8.5" x 4.75" x 4" |
| Magazine Capacity | N/A | N/A | 50" ~150 Cases | 50" ~150 Cases | 50" ~150 Cases | N/A | 50" ~150 Cases |
| Case Modification Available | N/A | N/A | N | N | Y | N/A | Y |
| Washdown Option | IP54 | IP54 | IP54 | IP54 | IP54 | IP54 | IP54 |
| Glue Version | N/A | N/A | Y | Y | N | N/A | N |
| Opposite Case Hand Option | N/A | N/A | N | N | Y | N/A | Y |
| Std. Voltage | 240V/3PH | 240V/3PH | 240V/3PH | 240V/3PH | 240V/3PH | 240V/3PH | 240V/3PH |
| SCFM - 80 PSI - 3/4 Supply Line | 84 SCFM | 84 SCFM | 17 SCFM | 20 SCFM | 13 SCFM | 30 SCFM | 17 SCFM |
| Footprint | 9'7" x 6'6" x 10'7" | 12' x 7'5" x 12' | 8'3" x 10'6" x 10'7" | 8'3" x 10'6" x 10'7" | 13'6" x 10'7" x 7'4" | 14'3" x 5'8" x 11'10" | 8'3" x 10'6" x 10'7" |
| Approx. Shipping Weight | ~2500 lbs. | ~2500 lbs. | ~4000 lbs. | ~4000 lbs. | ~4500 lbs. | ~4000 lbs. | ~4500 lbs. |
| Std. Finish | Steel Plus 316 is a two component, water base epoxy filled with 316 stainless steel flake. Finish Color is a Steel-It Grey and is USDA and FDA accepted. | | | | | | |
| Controls | AB COMPACT LOGIX PLC with PV+ Color TS | | | | | | |