



TRAY FORMER SPECIFICATIONS

TRAY FORMER MODEL SPECIFICATIONS

SPECIFICATIONS	HTF 35G	HTF12G	HTF 10	HTF 8	TF 40G
Max. Speed	35 TPM	12 TPM	10 TPM	8 TPM	40 TPM
Tray Style	4- Corner Glue	4- Corner Glue/ Custom	Tuck Fold	Tuck Fold/ Custom	4- Corner Glue
Max. Tray Range	24" x 24" x 9"	28" x 28" x 11"	24" x 24" x 9"	28" x 28" x 11"	20" x 16" x 6"
Min. Tray Range	8.5" x 8.5" x 2"	12" x 12" x 2"	8.5" x 8.5" x 8.5"	12" x 12" x 12"	6" x 6" x 2"
Magazine Capacity	400 - 450 cases				
Tray Modification Available	Y	Y	Y	Y	N
Washdown Option	N	N	N	N	N
Std. Voltage	240V/3PH				
SCFM - 80 PSI - 3/4 Supply Line	2.04 SCFM	2.04 SCFM	7.35 SCFM	7.35 SCFM	0.8 SCFM
Footprint	13'6" x 6' x 9'	16'4" x 7'5" x 11'	13'3" x 10' x 7'7"	16'2" x 6'7" x 11'	5'5" x 7'11" x 6'8"
Approx. Shipping Weight	~3000 lbs.	Weight Varies	~3000 lbs.	Weight Varies	~2000 lbs.
Std. Finish	Steel Plus 316 is a two component, water base epoxy filled with 316 stainless steel flake. Finish Color is a Steel-It Grey and is USDA and FDA accepted.				
Controls	AB COMPACT LOGIX PLC with PV+ Color TS				
Available Options	Low Tray, Low Glue, Extended Magazine, Casters (Except on HTF models), Stack Lights, Elevation Kits, Change Part Carts, Spare Parts				